NX Driver

New high-precision, compact NX Driver Created!

Achieve the reduction in size and weight with inherited the performance of KX & NX driver which get a favorable reception to the optimization screw driving.

All fastening conditions can be adjusted to perform the perfect fastening.

The fastening conditions that Torque, Speed and Angle can be input directly with numerical value. In response to the screw and workpiece, the fastening condition will be changed for each fastening point, which can be able to install the programs up to 16 numbers. It also performs high accuracy fastening with two-stage fastening process.

Inherit the high performance to the screw driving

Provide two kind of screw driving method, one Torque monitoring and the other Torque control driving, which it can be met the most suitable method for all kind of workpieces.

Innovate a new AC servo motor

It will be used the most suitable motor for screw driving and make it possible to the high accuracy control. Take care of the trouble by introducing high resolution Encoder with a function to detect error quickly. Reinforced cable connections prevent cable damage.

Equipped with USB and RS485 Ports

It equipped with USB port to communicate with PC. Standard USB cable as commercial item can be used. It is easy to use communication software and improves the performance of maintenance. Additional RS485 port to use communicate with the external device will be created simple network.




NITTO SEIKO CO., LTD.


Specifications

Tool unit model	※ 1	NX008T2-03S*-20	NX020T2-07■*-20	NX050T2-07■*-20	NX100T2-07■*-20
Setup torque range (N·m)	※ 2	0.2~0.8	0.5~2.0	1.0~5.0	2.5~9.0
Max. rotation speed (min ⁻¹)	% 3	1,200	840		
Output torque accuracy		3σ/x=5% or less		$3\sigma/\bar{x} = 3\%$ or less	
Torque sensor		Planetary gear type reaction torque sensor (strain gauge)			
Tool unit weight (kg)		0.6	1.0	1.1	1.2
Applicable controller model	※ 4	SD550T03-2020-■		SD550T05-2020-■	
Control method		Torque / Angle			
Number of programs		16 sets, max. (from 0 to 15)			
Self diagnostic function		Indication of system error number and external signal output			
Power source	※ 5	Single phase AC200~230V±10% 50/60Hz			
Max. power requirement (kVA	4)	0.6	0.45	0.6	0.75
Controller weight (kg)		0.75			


- ※1. 「■Jmark into the model number indicates the shape of output shaft as follows. M: M8 Thread, S: Square (9.5mm except NX008 / 6.35mm for NX008)
 ※2. If the following conditions will be needed the tightening test with actual Driver. If it is necessary, please feel free to ask. [*] mark into the version number.
- •It is required short cycle time. •It is need to keep the high torque value during tightening to the tapping screw. Rotating speed setting is limited by fastening condition.
- ※4. I praction into the model number indicates the optional processing function which analyze the wave form is included or not. (0: Not include, 2: Include)
 ※5. AC100-115V power supply is available with optional AC power unit.


Tool unit outside dimension (mm)





(Overall length)







Dimension of TU series

* Option

·Flange for installation


compatible flange attachment (mm)





Output shaft end dimension (mm)

M: M8 thread Square 10 (wrench flat)



Ø2. 1

Details of component

1 Tool Unit : 1pc ② Controller : 1pc

3 Motor Cable : 1pc Choose 3m or 10m(Option) %1 %2 4 Encoder Cable *1, *2 Choose 3m or 10m(Option) : 1pc ⑤ Sensor Cable **1 : 1pc Choose 3m or 10m(Option) 6 Power Connecter : 1pc (It doesn't include a cable which is optional) %3

7 I/O Connecter : 1pc (It doesn't include a cable which is optional) %3

8 Network Connecter : 1pc

X1 Choose 2m, 5m or 7.5m (Other length is option up to 10m)

※2 Model is different between NX008T2 and others.

3 Choose 2m, 3m, 4m, 7m or 10m

NITTO SEIKO CO., LTD. **Machinery Division**

Website: https://www.nittoseiko.co.jp/

Global sales head office:


2, Shiroyama, Ayabe city, Kyoto 623-0003, Japan Telephone / +81-773-42-1290 Fax / +81-773-43-1553

Controller outside dimension (mm)

30

75

4-M3 depth7



68.5

(76)

